



635nm 30mw Laser Diodes

Features:

Visible light: $635 \pm 10\text{nm}$

Low threshold current: $\leq 50\text{mA}$

Output power: $\geq 21\text{mW (CW)}$

Index guided single transverse mode

Standard TO-18 package ($\Phi = 5.6\text{mm}$)

50°C high temperature operation

Low astigmatism high reliability

Applications:

Indicator.

Point.

Absolute Maximum Ratings($T_c=25^\circ\text{C}$)

Parameter Units Symbol Rating

Optical power mW $P_o \geq 21$

Operating temperature $^\circ\text{C}$ T_{op} -10~50

Storage temperature $^\circ\text{C}$ T_{stg} -40~85

LD reverse voltage V $V_{RLD} \leq 2.4$

PD reverse voltage V $V_{RPD} \geq 30$

Optical and electrical characteristics($T_c=25^\circ\text{C}$) $\leq \geq \pm$

Parameter Symbol Typical Unit

Lasing wavelength λ $635 \pm 10\text{ nm}$

Optical power $P_o \geq 21\text{ mw}$

Threshold current $I_{th} \leq 40\text{ mA}$

Operating current $I_{op} \leq 70\text{ mA}$

Operating voltage $V_{op} \leq 2.3\text{ V}$

Monitoring current $I_m \geq 0.3\text{ mA}$